

**IN THE CLAIMS:****1. (Original)**

A device for placement between the hands of a person performing chest compressions and the chest of a patient or a manikin, characterised in comprising:

a first part and a second part, said parts being moveable towards each other when a compression is performed,

a return means between said parts for moving said parts away from each other again when the compression is relieved,

a mechanical sound generator between said parts for generating a sound when said parts are moved towards each other with a force exceeding a pre-defined value,

an electric power source between said parts,

an electronic sound generating means between said parts, and coupled to said power source, for generating a repeating sound indicating a desired compression rate, and

a switch between said parts, said switch being operated by the movement of said parts towards each other, and said switch operably coupling said power source to said electronic sound generating means.

**2. (Original)**

Device according to claim 1, characterised in that said switch is integrated in said mechanical sound generator.

**3. (Currently Amended)**

Device according to claim 1 ~~claims 1 or 2~~, characterised in that said switch includes a microphone or other piezoelectric means that picks up the sound energy created by said mechanical sound generator and utilizes this energy to couple said power source to said electronic sound generating means.

**4. (Currently Amended)**

Device according to claim 1 ~~any of the preceding claims~~, characterised in that the first occurrence of the repeating sound occurs after the first occurrence of the mechanical sound.

## 5. (Currently Amended)

Device according to claim 1 ~~any of the preceding claims~~, characterised in that the repeating sound may be switched off and on by pressing the first and the second parts together with a sufficient force over a specified period of time.

## 6. (Original)

A device for placement between the hands of a person performing chest compressions and the chest of a patient or a manikin, characterised in comprising:

a first part and a second part, said parts being moveable towards each other when a compression is performed,

a return means between said parts for moving said parts away from each other again when the compression is relieved, and

a mechanical sound generator between said parts for generating a sound when said parts are moved towards each other with a force exceeding a pre-defined value,

said mechanical sound generator comprising a plate suspended at one end thereof, the opposite end of said plate being free, said plate being shaped to generate a sound when said force exceeding a predetermined value is exerted on said free end of said plate.

## 7. (Currently Amended)

Device according to claim 1 ~~any of the preceding claims~~, characterised in that said return means is a pliable gasket extending along the perimeter of said parts.

## 8. (Original)

A device for placement between the hands of a person performing chest compressions and the chest of a patient or a manikin, characterised in comprising:

a first part and a second part, said parts being moveable towards each other when a compression is performed,

a return means between said parts for moving said parts away from each other again when the compression is relieved,

an electric power source between said parts,

an electronic sound generating means between said parts, and coupled to said power source,

and

a switch between said parts, said switch being operated by the movement of said parts towards each other, and said switch operably coupling said power source to said electronic sound generating means.

9. (Original)

Device according to claim 8, characterised in that the sound generator generates a repeating sound indicating a desired compression rate.

10. (Currently Amended)

Device according to claim 8 ~~claim 8 or 9~~, characterised in that said sound generating means generates a sound when said parts are moved towards each other with a force exceeding a pre-defined value.

11. (Currently Amended)

Device according to claim 8 ~~claim 8, 9 or 10~~, characterised in further comprising a mechanical sound generator between said parts for generating a sound when said parts are moved towards each other with a force exceeding a pre-defined value.

12. (Currently Amended)

Device according to claim 1 ~~any of the preceding claims 1, 2, 3, 4, 5, 8, 9, 10 or 11~~, characterised in that said power source is a power generator, generating electric power from the movement of said parts.

13. (Currently Amended)

Device according to claim 1 ~~any of the preceding claims~~, characterised in that the outside surfaces of said parts are made from or at least partly covered with a material with a high coefficient of friction, preferably also being pliable, to avoid slipping and hurting.

14. (Original)

A device for placement between the hands of a person performing chest compressions and the chest of a patient or a manikin, characterised in comprising:  
a first part and a second part, said parts being moveable towards each other when a compression is performed,